

# TECHNICAL BULLETIN

Issue Date : March 29, 2000 Revised: February 5, 2013 No. 01-115-00

# Air and Water Infiltration Medallion II 24 Ga.

On January 3, 2000, McElroy Metal, Inc. tested its Medallion II Panel for air leakage and water penetration.

#### **TEST METHODS:**

Air Leakage: ASTM E1680-95, "Rate of Air Leakage Through Exterior Metal Roof Panel

Systems"

Water Penetration: ASTM E1646-95, "Water Penetration of Exterior Metal Roof Panel Systems

by Uniform Static Air Pressure Difference"

### **TEST SPECIMEN:**

McElroy Metal, Inc. 24 Ga. 12 in. wide Medallion II Roof Panel over #30 underlayment with 6 inch overlaps. Panels were attached to 5/8" (nominal) plywood using (2) #10-12 Pancake Head woodgrip fastener per clip, with clips at 2 feet on center. All plywood butt joints were sealed with silicone sealant.

## **TEST RESULTS:**

12" 24\* Ga.

	A	Air Infiltration	1	Water Penetration			
Specimen	Static Pressure Differential (psf)	Air Infiltration rate (cfm/lf)	Air Infiltration rate (cfm/sf)	Static Pressure Differential (psf)	Rate (gal./hr/sf)	Test Duration (min)	Water Infiltration
Medallion II 12" 24* Ga.	+6.24	0.031	0.029	6.24	5	15	None
Medallion II 12" 24* Ga.	+1.57	0.014	0.013				
Medallion II 12" 24* Ga.	-6.24	0.019	0.017				
Medallion II	-1.57	0.012	0.011				

Test Report No.: T102-00 Dated: January 5, 2000

CORPORATE OFFICE SHREVEPORT, LOUISIANA

<sup>\*</sup>Test results are valid for heavier gauges or thicknesses.