138T ASV EAVE

** CLEARANCE REQUIRED FOR THERMAL MOVEMENT #14-10 X 1-1/2" HWH TYPE-A FASTENER (@ 1'-0" O.C.) 9" (MAX.) 138T PANEL PYTHON VENT -4" 138T ASV CLIP BEARING PLATE BUTYL TUBE SEALANT -(APPLY UP VERTICAL LEG APPROVED HIGH TEMP. PEEL & STICK MAKING SURE SEALANT UNDERLAYMENT UNDER VALLEY TRIM AND ENTERS HEM) FOR FIRST 3'-0" FROM EAVE, LAPPED OVER EAVE TRIM. #30 FELT THEREAFTER. VENTED EAVE/RIDGE TRIM (NOT BY MCELROY) (MT-186)(PRE-DRILL 5/16" DIA. HOLES RIGID INSULATION @ 1'-0" O.C.) (NOT BY MCELROY) VAPOR BARRIER 3/32" X 1" ROLL TAPE SEALANT (RECOMMENDED) (CONT. ALONG EAVE) (NOT BY MCELROY) 22GA. METAL DECK EAVE FLASHING (NOT BY MCELROY) (MT - 28)ROOF LINE #9-15 X 1" HWH TYPE A (NOT BY MCELROY) FASTENER (@ 1'-0" O.C.) #12-13 DEKFAST FASTENER (2 PER CLIP) #10-12 X 1" TYPE A PANCAKE HEAD FASTENER (@ 5'-0" O.C.) WOOD BLOCKING (NOT BY MCELROY)

