

SAFETY DATA SHEET

Revision date 15-Jan-2025

Version 21

Supersedes Date: 08-Jan-2025

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code 432R1065

Product Name FLUROPON SR CHARCOAL

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Sherwin-Williams Company
101 W. Prospect Avenue
Cleveland, OH 44115

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

Classification

| | |
|--|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 1B |
| Specific target organ toxicity (single exposure) | Category 3 |
| Flammable liquids | Category 3 |

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Flammable liquid and vapor
Causes serious eye irritation
Suspected of causing cancer
May damage fertility or the unborn child
May cause drowsiness or dizziness

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Keep cool.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

OTHER HAZARDS

Not applicable.

UNKNOWN ACUTE TOXICITY .0002% of the mixture consists of ingredient(s) of unknown toxicity

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No. | Weight-% |
|---|------------|--------------|
| Isophorone | 78-59-1 | 10 - 25 |
| Propylene glycol monomethyl ether acetate | 108-65-6 | 10 - 25 |
| Chromium iron oxide | 12737-27-8 | 5 - 10 |
| Titanium dioxide | 13463-67-7 | 3 - 5 |
| Ethylene glycol monobutyl ether acetate | 112-07-2 | 3 - 5 |
| Dimethyl phthalate | 131-11-3 | 1 - 3 |
| Diisobutyl ketone | 108-83-8 | 1 - 3 |
| Toluene | 108-88-3 | 0.3 - 1 |
| 2-Butoxyethanol | 111-76-2 | 0.3 - 1 |
| Formaldehyde | 50-00-0 | 10 - <90 ppm |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

Description of first aid measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES**Suitable extinguishing media**

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons:

Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep tightly closed in a dry and cool place.

Incompatible materials

Strong bases. Strong oxidizing agents. Acids.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---|-------------------------------|---|--|
| Isophorone 78-59-1 | Ceiling: 5 ppm | TWA: 25 ppm TWA: 140 mg/m ³ | IDLH: 200 ppm TWA: 4 ppm TWA: 23 mg/m ³ |
| Chromium iron oxide 12737-27-8 | TWA: 0.5 mg/m ³ Cr | TWA: 0.5 mg/m ³ Cr Ceiling: 0.1 mg/m ³ CrO ₃ applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect | IDLH: 15 mg/m ³ Cr(VI) IDLH: 25 mg/m ³ Cr(III) TWA: 0.0002 mg/m ³ Cr TWA: 0.5 mg/m ³ Cr |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| Ethylene glycol monobutyl ether acetate 112-07-2 | TWA: 20 ppm | | TWA: 5 ppm TWA: 33 mg/m ³ |
| Dimethyl phthalate 131-11-3 | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ | IDLH: 2000 mg/m ³ TWA: 5 mg/m ³ |
| Diisobutyl ketone 108-83-8 | TWA: 25 ppm | TWA: 50 ppm TWA: 290 mg/m ³ | IDLH: 500 ppm TWA: 25 ppm TWA: 150 mg/m ³ |
| Toluene 108-88-3 | TWA: 20 ppm | TWA: 200 ppm Ceiling: 300 ppm | IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ |
| 2-Butoxyethanol 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m ³ S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³ |
| Formaldehyde 50-00-0 | Ceiling: 0.3 ppm | TWA: 0.75 ppm STEL: 2 ppm see 29 CFR 1910.1048 | IDLH: 20 ppm Ceiling: 0.1 ppm 15 min TWA: 0.016 ppm |

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin and body protection

Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|-------------------------------|----------------------------------|
| Physical state | Liquid |
| Appearance | No information available |
| Odor | Ketones and their derivatives |
| Color | grey |
| Odor Threshold | No information available |
| pH - VALUE 1 | No information available |
| Melting point/freezing point | No information available |
| Boiling point / boiling range | No information available °C / °F |
| flash point | 28 °C / 82.4 °F |
| evaporation rate | No information available |
| Flammability (solid, gas) | No information available |
| Flammability Limit in Air | |
| Upper flammability limit: | 13.1 |
| Lower flammability limit: | .5 |
| Vapor pressure | 4.9 |
| Relative vapor density | No information available |
| Density (lbs per US gallon) | 10.77 |
| specific gravity | 1.29 |
| Solubility(ies) | Insoluble in water |
| Partition coefficient | No information available |
| Autoignition temperature | 280 °C / 536 °F |
| Decomposition temperature | No information available |
| Kinematic viscosity | No information available |
| Dynamic viscosity | No information available |

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous polymerization None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong bases. Strong oxidizing agents. Acids.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO₂). Hydrogen fluoride.

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

Not applicable

Ingestion

Not applicable

Inhalation

May cause drowsiness or dizziness

Numerical measures of toxicity - Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|-----------------------|--|--------------------------|
| Isophorone 78-59-1 | = 1870 mg/kg (Rat) | = 1700 mg/kg (Rat) = 1390 mg/kg (Rat) | = 7 mg/L (Rat) 4 h |
| Propylene glycol monomethyl ether acetate 108-65-6 | = 8532 mg/kg (Rat) | > 5 g/kg (Rabbit) | - |
| Chromium iron oxide 12737-27-8 | - | - | - |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Ethylene glycol monobutyl ether acetate 112-07-2 | = 2400 mg/kg (Rat) | = 1500 mg/kg (Rabbit) | > 400 ppm (Rat) 4 h |
| Dimethyl phthalate 131-11-3 | = 6800 mg/kg (Rat) | > 20 mL/kg (Rabbit) > 4800 mg/kg (Rat) | - |
| Diisobutyl ketone 108-83-8 | = 5750 mg/kg (Rat) | = 16 g/kg (Rabbit) | > 2300 ppm (Rat) 4 h |
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat) 4 h |
| 2-Butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 99 mg/kg (Rabbit) | = 450 ppm (Rat) 4 h |
| Formaldehyde 50-00-0 | = 100 mg/kg (Rat) | = 270 mg/kg (Rabbit) | = 0.578 mg/L (Rat) 4 h |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2,901.80 mg/kg
 ATEmix (dermal) 5,421.30 mg/kg
 ATEmix (inhalation-dust/mist) 20.80 mg/l
 ATEmix (inhalation-vapor) 103.40 mg/l

UNKNOWN ACUTE TOXICITY .0002% of the mixture consists of ingredient(s) of unknown toxicity

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints

since the pigment is bound to other materials.

| Chemical name | ACGIH | IARC | NTP | OSHA |
|--|-------|----------|-------|------|
| Isophorone 78-59-1 | A3 | | | |
| Titanium dioxide 13463-67-7 | | Group 2B | | X |
| Ethylene glycol monobutyl ether acetate 112-07-2 | A3 | | | |
| 2-Butoxyethanol 111-76-2 | A3 | | | |
| Formaldehyde 50-00-0 | A2 | Group 1 | Known | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - *Animal Carcinogen*. A2 - *Suspected Human Carcinogen*.

IARC (International Agency for Research on Cancer)

Group 2B - *Possibly Carcinogenic to Humans*. Group 1 - *Carcinogenic to Humans*.

NTP (National Toxicology Program)

Known - *Known Carcinogen*.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - *Present*.

Skin corrosion/irritation Not applicable

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitization Not applicable

Respiratory sensitization Not applicable

Germ cell mutagenicity Not applicable

Carcinogenicity Suspected of causing cancer

Reproductive Toxicity May damage fertility or the unborn child

Specific target organ toxicity (single exposure) May cause drowsiness or dizziness

Specific target organ toxicity (repeated exposure) Not applicable

Aspiration hazard Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

14.1 UN number or ID number

DOT
UN1263

IMDG
UN1263

IATA
UN1263

| | | | |
|---|---|--|--------------------------|
| 14.2 Proper shipping name | Paint | Paint | Paint |
| 14.3 Hazard Class | 3 | 3 | 3 |
| 14.4 Packing Group | III | III | III |
| 14.5 Environmental hazards | | | |
| 14.6 Special Provisions | 367, B1, B52, B131, IB3, T2, TP1, TP29 Emergency Response Guide Number 128 | 163, 223, 367, 955 EmS-No. F-E, S-E | A3, A72, A192 |
| 14.7 Maritime transport in bulk according to IMO instruments | | | No information available |

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

International Inventories

| | |
|---|--|
| TSCA - United States Toxic Substances Control Act Section 8(b) Inventory | All components are listed or exempt from listing. (Active List). |
| DSL - Canadian Domestic Substances List | All components are listed or exempt from listing |

US Federal Regulations

All data given below are **MAXIMUM THEORETICAL VALUES** based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate **MAXIMUM THEORETICAL VALUES** using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

| Chemical name | SARA 313 - Threshold Values % | Metals | Hazardous air pollutants (HAPs) content |
|--|-------------------------------|----------|---|
| Isophorone 78-59-1 10 - 25 | | | Present |
| Chromium iron oxide 12737-27-8 5 - 10 | 1 | Chromium | Present |
| Ethylene glycol monobutyl ether acetate 112-07-2 3 - 5 | 1 | | Present |
| Dimethyl phthalate 131-11-3 1 - 3 | 1 | | Present |
| Toluene 108-88-3 0.3 - 1 | 1 | | Present |
| Lead (ppm) SARA 313 - Threshold Value - 0% .098 | | | |
| Mercury (ppm) SARA 313 - Threshold Value - 0% .0005 | | | |

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|-----------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Isophorone 78-59-1 | | X | X | |
| Chromium iron oxide 12737-27-8 | | X | | |
| Dimethyl phthalate 131-11-3 | | X | X | |
| Toluene 108-88-3 | 1000 lb | X | X | X |
| Formaldehyde | 100 lb | | | X |

| | | | |
|---------|--|--|--|
| 50-00-0 | | | |
|---------|--|--|--|

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|--------------------------------|--------------------------|----------------|--|
| Isophorone 78-59-1 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| Dimethyl phthalate 131-11-3 | 5000 lb | | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| Toluene 108-88-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |
| Formaldehyde 50-00-0 | 100 lb | 100 lb | RQ 100 lb final RQ RQ 45.4 kg final RQ |

US State Regulations

Rule 66 status of product

Photochemically reactive.

California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

| |
|--|
| Chemical name |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| Isophorone 78-59-1 |
| Propylene glycol monomethyl ether acetate 108-65-6 |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| Chromium iron oxide 12737-27-8 |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| Titanium dioxide 13463-67-7 |
| Ethylene glycol monobutyl ether acetate 112-07-2 |
| Dimethyl phthalate 131-11-3 |
| Diisobutyl ketone 108-83-8 |
| Toluene 108-88-3 |

Section 16: OTHER INFORMATION

HMIS

Health hazards 2*

* = Chronic Health Hazard

Flammability 3

Physical hazards 0

Personal Protection X

Supplier Address

Valspar Coatings The Valspar Corporation Valspar Coil

701 Shiloh Rd.
Garland, TX 75042
972-276-5181

901 N. Greenwood Ave.
Kankakee, IL 60901
815-933-5561

5501 E. Slauson Ave.
Los Angeles, CA 90040
323-726-7272

Prepared By

Product Stewardship

Revision date

15-Jan-2025

Revision Note

No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet