MCELROY METAL

GALVALUME[®] SUBSTRATE WITH FLUROPON PRINT COAT KYNAR 500[®] (PVDF) COATINGS, SUCH AS COR-TEN AND WOOD GRAIN PATTERNS LIMITED WARRANTY APPLICABLE PRODUCTS: ALL MCELROY PRINT COAT PVDF COATED PRODUCTS WITH GALVALUME SUBSTRATES

McElroy Metal, Inc. ("McElroy") warrants to the purchaser of McElroy panels using Fluropon Print Coat Kynar 500® or Hylar 5000® (PVDF) coating systems that when used in exterior applications the coating system will meet the following standards. For warranty terms on special and/or non-standard colors, please contact a McElroy representative.

- 1. For a period of 40 years from date of shipment, coating exhibits cracking, flaking, or peeling (loss of adhesion) to an extent that is apparent on ordinary outdoor visual observation. Failure due to substrate corrosion is not a covered Warranty Condition.
- 2. For a period of 30 years from date of shipment, coating chalks in excess of ASTM D-4214 method A number 8 rating when properly maintained as described herein.
- 3. Within 20 years from the date of shipment, Fluropon Print Coat will remain intact and distinguishable.

McElroy Metal also warrants to the purchaser that McElroy Metal's hot dipped aluminum-zinc alloy coated GALVALUME (TM) sheet steel sold for use as painted roofing and siding panels, if erected within the United States will not rupture, fail structurally, or perforate due to exposure to normal environmental conditions for the warranty period listed below.

• 50 years for AZ 50 Galvalume substate with Fluropon PVDF coating

Warranties are subject to the conditions, limitations and exclusions set forth below:

Coating Warranty

If any panels fail to comply with the coating warranty specifications set forth above, McElroy will pay for labor and material reasonably necessary to repaint, repair or replace, at our option, the metal panels showing the Warranty Conditions. The Warranty Benefits shall not exceed the costs of the then-current panel and labor to replace the affected metal panels (not including any accessories or attachments).

Substrate Warranty

If any panels fail to comply with the substrate warranty specifications set forth above, McElroy Metal's liability for breach of this warranty shall be limited exclusively to the cost of either repairing nonconforming panels, or at McElroy Metal's sole option replacing nonconforming panels. McElroy Metal shall not in any event be liable for the cost of labor expended by others on any nonconforming sheet.

McElroy shall not be held liable for any special, indirect or consequential damages to anyone by reason of the fact that such panels are nonconforming. These Warranties will continue to apply to any metal panels that were repainted, repaired or replaced due to a Warranty Condition, but only for the unexpired portion of the Warranty period applicable to the original

Dart. THIS WARRANTY SHALL BE SUBJECT TO THE FOLLOWING CONDITIONS, LIMITATIONS AND EXCLUSIONS:

A. This warranty covers only panels erected in the continental United States, which are exposed to normal weather and atmospheric conditions.

All claimsofiled surver antis is a contribute be mail to provide a synthetic provide sent and the sent and th

- 1. the formation of rust on the panel edges;
- 2. acts of God, falling objects, external forces, explosions, fire, riots, civil commotions, acts of war, radiation, harmful gases, harmful fumes, salt atmosphere or standing water due to failure to provide adequate slope and drainage;

MCELROY METAL

GALVALUME[®] SUBSTRATE WITH FLUROPON PRINT COAT KYNAR 500[®] (PVDF) COATINGS, SUCH AS COR-TEN AND WOOD GRAIN PATTERNS LIMITED WARRANTY APPLICABLE PRODUCTS: ALL MCELROY PRINT COAT PVDF COATED PRODUCTS WITH GALVALUME SUBSTRATES

- 3. failure to properly insulate panels from direct contact, fallout or run-off from dissimilar metals such as copper, lead, nickel, stainless steel, etc., contact with damp insulation, chemicals, fumes, ash, debris, soil, vegetation, animal waste, decaying materials, wet absorptive materials, concrete, cement dust, animal waste or other foreign or corrosive materials from contact with or in close proximity to the panel;
- 4. paint adhesion loss and/or staining as a result of excessive sealant or failure to remove steel debris/iron particles that come in contact with the panel surface;
- 5. significant differences in insulation below coated metal panel;
- 6. use in manner not intended or improper storage or handling, including but not limited to damage from condensation on the panels attributable to improper handling;
- 7. conditions / circumstances where corrosive fumes or condensates are generated or released inside the building;
- minute fracturing which may occur in proper fabrication of the building parts. Bends less than 2T inside bend diameter for sheet thickness 0.030" and thinner, and less than 4T for sheet thickness 0.031" and thicker;
- 9. slopes of the roof or sections of the roof flatter than 1/4:12;
- 10. if panels are applied without protection over lumber which has been treated with preservatives or fire-resistant materials, regardless whether such treatments are present with or without the knowledge of the buyer, the owner or any other party. This exclusion shall include, but is not limited to, lumber which has been treated with pentachlorophenol, chromated copper-arsenate salts, creosote, fluochrome arsenate phenol, alkaline copper quaternary, or any similar treatment for fire and rot resistance. Protection of lumber as provided for in the exclusion shall be defined as any barrier that prevents the transfer of moisture and salts between the treated lumber and pre-finished metal panel;
- abnormal corrosive atmospheric conditions. This exclusion includes, but is not limited to, contamination from external sources such as manufactured chemicals and salt spray, and internal contamination created by improper ventilation (design or operational defects) or improper housekeeping;
- 12. discontinuities in the paint film as a result of damage during installation or use of the building e.g., scratches;
- 13. attachment or adhesion of materials or items such as snow guards and solar panels to the metal panels;
- 14. damage due to improper forming, scouring, cleaning procedures or use of any bleach-based cleaners;
- 15. any condition, which occurs in any chemically aggressive environment containing salts, or other chemicals, whether naturally occurring or caused by man, are stored/installed in an environment that includes a high degree of humidity, sand, dirt or grease;
- 16. design flaws or elements that would result in moisture (water) or other foreign materials to accumulate resulting in excessive exposure to moisture or foreign material, including dirt, leaves, soil, vegetation, mold, mildew, fungus and rubbish.
- E. McElroy shall have no obligations under this warranty unless and until McElroy receives payment in full for the materials furnished.
- F. The supplier of the Galvalume substrate and paint coating applied to McElroy panels and the applicator of the paint coating has made certain warranties to McElroy which are same (or substantially similar) to the warranties made by McElroy under this limited warranty. This limited warranty shall be of no further force or effect if such supplier, or its successors or assigns, can no longer perform its obligations under the substrate and coating system warranties made to McElroy.

THERE ARE NO OTHER GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, WHICH EXTEND BEYOND THE DESCRIPTION AS STATED HEREIN, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS OF PURPOSE. McELROY METAL SHALL NOT BE RESPONSIBLE FOR ANY INDIRECT OR CONSEQUENTIAL DAMAGES (SUCH AS DAMAGES TO THE CONTENTS OR FURNISHINGS OF ANY BUILDING) OR ANY LOSS OF ANY KIND WHATSOEVER.