

## SAFETY DATA SHEET

Revision date 29-Dec-2016

Version 4

Supersedes Date: 17-Aug-2016

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

**Product Code** 

435RZ268

**Product Name** 

FLUROPON SR HARTFORD GREEN

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar Corporation PO Box 1461 Minneapolis, MN 55440

E-mail address msds@valspar.com

Emergency telephone number

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

## **Section 2: HAZARDS IDENTIFICATION**

## Classification

Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

## Label elements



#### Signal word

#### WARNING

#### **HAZARD STATEMENTS**

Flammable liquid and vapor
Causes serious eye irritation
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause respiratory irritation

#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

## **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction.

#### **STORAGE**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Not applicable.

## **OTHER HAZARDS**

Not applicable.

## **UNKNOWN ACUTE TOXICITY**

0% of the mixture consists of ingredient(s) of unknown toxicity.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Isophorone	78-59-1	10 - 25
Ethylene glycol monobutyl ether acetate	112-07-2	1 - 3
C.I. Pigment Green 50	68186-85-6	1 - 3
Titanium dioxide	13463-67-7	0.3 - 1
Toluene	108-88-3	0.3 - 1
Formaldehyde	50-00-0	10 - 100 ppm

## **Section 4: FIRST AID MEASURES**

#### **First Aid Measures**

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

## Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

## Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

## Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

## For emergency responders

Use personal protection recommended in Section 8.

## **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### Methods and material for containment and cleaning up

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

## **Section 7: HANDLING AND STORAGE**

#### Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

## **General Hygiene Considerations**

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

## Conditions for safe storage, including any incompatibilities

## **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep tightly closed in a dry and cool place.

#### Incompatible materials

Strong bases. Strong oxidizing agents. Acids.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

## **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isophorone 78-59-1	Ceiling: 5 ppm	TWA: 25 ppm TWA: 140 mg/m³	IDLH: 200 ppm TWA: 4 ppm TWA: 23 mg/m³
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm		TWA: 5 ppm TWA: 33 mg/m <sup>3</sup>
C.I. Pigment Green 50 68186-85-6			IDLH: 10 mg/m³ Ni TWA: 0.015 mg/m³ except Nickel carbonyl Ni
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³
Formaldehyde 50-00-0	Ceiling: 0.3 ppm	TWA: 0.75 ppm STEL: 2 ppm see 29 CFR 1910.1048	IDLH: 20 ppm Ceiling: 0.1 ppm 15 min TWA: 0.016 ppm

## **Appropriate engineering controls**

## **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin and body protection

Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### **Thermal Protection**

No information available

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state liquid

Appearance No information available

Odor Solvent Color green

Odor Threshold
pH value
No information available
No information available
No information available
No information available

Boiling point / boiling range No information available °C / °F

flash point 28 °C / 82 °F

evaporation rate

No information available
Flammability (solid, gas)

No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor Pressure
vapor density

No information available
No information available
No information available

Density (lbs per US gallon) 10.66 specific gravity 1.28

Solubility(ies)

Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity

No information available

Other information

## **Section 10: STABILITY AND REACTIVITY**

**Reactivity** No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

**Hazardous polymerization**None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

**Incompatible materials** Strong bases. Strong oxidizing agents. Acids.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Hydrogen fluoride.

## **Section 11: TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

#### Eye contact

Causes serious eye irritation

Skin Contact Not applicable Ingestion Not applicable

Inhalation

May cause respiratory irritation

#### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isophorone 78-59-1	= 1870 mg/kg (Rat)	= 1390 mg/kg ( Rat ) = 1700 mg/kg ( Rat )	= 7 mg/L (Rat) 4 h
Ethylene glycol monobutyl ether acetate 112-07-2	= 2400 mg/kg (Rat)	= 1480 mg/kg(Rabbit)	-
C.I. Pigment Green 50 68186-85-6	-	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L (Rat)4 h
Formaldehyde 50-00-0	= 100 mg/kg ( Rat )	= 270 mg/kg ( Rabbit )	= 0.578 mg/L (Rat) 4 h

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2449 Mg/kg
ATEmix (dermal) 4986 Mg/kg
ATEmix (inhalation-dust/mist) 91.1 mg/l
ATEmix (inhalation-vapor) 668 mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

## **Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints

since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isophorone 78-59-1	А3			
Ethylene glycol monobutyl ether acetate 112-07-2	А3			
C.I. Pigment Green 50 68186-85-6		Group 2B		X

Titanium dioxide 13463-67-7		Group 2B		Х
Formaldehyde 50-00-0	A2	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen. A2 - Suspected Human Carcinogen. IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans. Group 1 - Carcinogenic to Humans.

NTP (National Toxicology Program)

Known - Known Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Not applicable

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitization Not applicable Not applicable Respiratory sensitization Not applicable Germ cell mutagenicity

Carcinogenicity Suspected of causing cancer

**Reproductive Toxicity** Suspected of damaging fertility or the unborn child

Specific target organ toxicity (single May cause respiratory irritation

exposure)

Specific target organ toxicity

(repeated exposure)

Not applicable

**Aspiration hazard** Not applicable

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity** 

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

**Bioaccumulation** 

No information available

**Mobility** 

No information available

Other adverse effects No information available

## **Section 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

## **Section 14: TRANSPORT INFORMATION**

	<u>DOT</u>	<u>IMDG</u>	<u>IATA</u>
14.1 UN/ID no	UN1263	UN1263	UN1263
14.2 Proper shipping name	Paint	Paint	Paint

14.3 Hazard Class 14.4 Packing Group III Ш Ш

14.5 Environmental hazard Not applicable

B1, B52, IB3, T2, TP1, TP29, 367 14.6 Special Provisions 163, 223, 367 955 A3, A72, A192

**Emergency Response Guide** EmS-No Number F-E, S-E 128

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

## **Section 15: REGULATORY INFORMATION**

#### **International Inventories**

**DSL** - Canadian Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing.

All components are listed or exempt

from listing

## **US Federal Regulations**

Chemical Name	SARA 313 - Threshold Values %	Hazardous air pollutants (HAPs) content
Isophorone 78-59-1 10 - 25		Present
Chromium iron oxide 12737-27-8 5 - 10	1	Present
Dimethyl phthalate 131-11-3 3 - 5	1	Present
Ethylene glycol monobutyl ether acetate 112-07-2 1 - 3	1	Present
C.I. Pigment Green 50 68186-85-6 1 - 3	0.1	Present
Toluene 108-88-3 0.3 - 1	1	Present

## SARA 311/312 Hazard Categories

Acute health hazard Yes **Chronic Health Hazard** Yes Fire hazard Yes Sudden release of pressure hazard No **Reactive Hazard** No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Isophorone 78-59-1		X	X	
C.I. Pigment Green 50 68186-85-6		X		
Toluene 108-88-3	1000 lb	X	X	Х
Formaldehyde 50-00-0	100 lb			Х

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Isophorone	5000 lb		RQ 5000 lb final RQ
78-59-1			RQ 2270 kg final RQ
Toluene	1000 lb		RQ 1000 lb final RQ
108-88-3			RQ 454 kg final RQ
Formaldehyde	100 lb	100 lb	RQ 100 lb final RQ
50-00-0			RQ 45.4 kg final RQ

## **US State Regulations**

## Rule 66 status of product

Photochemically reactive.

#### **California Proposition 65**

WARNING! This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## U.S. EPA Label information

EPA Pesticide registration number Not applicable

## **U.S. State Right-to-Know Regulations**

Chemical Name
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Isophorone 78-59-1
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Chromium iron oxide 12737-27-8
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Dimethyl phthalate 131-11-3
Ethylene glycol monobutyl ether acetate 112-07-2
C.I. Pigment Green 50 68186-85-6
Toluene 108-88-3

## **Section 16: OTHER INFORMATION**

## **HMIS**

## **Supplier Address**

Valspar CoatingsThe Valspar CorporationValspar Coil701 Shiloh Rd.901 N. Greenwood Ave.5501 E. Slauson Ave.Garland, TX 75042Kankakee, IL 60901Los Angeles, CA 90040972-276-5181815-933-5561323-726-7272

Prepared By Product Stewardship

Revision date 29-Dec-2016

Revision Note No information available

#### **Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**